

APPENDIX 3: SPRING MOUNT LEVELING SCREW CHART

LO/TUNED™ SPRING MOUNT LEVELING SCREW SPECIFICATION SHEET														
Leveling Screw Model	Good for Foot Thickness Up To:				Leveling Screw Specifications						Lock Nut		Washer	
	Isolator Models				Pitch & Length			Head Height	Distance Across Flats	Radius at End	Distance Across Flats	Thickness	Diameter	Thickness
	VSML1208	VSML1608	VSML2112	VSXL2409	Dia.	TPI	Length							
.625M4	0.4				0.625	-11	4	0.38	0.438	3	0.94	0.55	1.31	0.09
.625M5	1.4						5							
.625M6	2.4						6							
.625M8	4.4						8							
.625M10	6.4						10							
.75M4	0.5				0.750	-10	4	0.38	0.5	3	1.13	0.42	1.47	0.14
.75M6	2.5						6							
.75M8	4.5						8							
.75M10	6.5						10							
1M4	0.4	0.3			1.00	-14	4	0.50	0.75	3	1.50	0.55	2.00	0.14
1M5	1.4	1.3					5							
1M6	2.4	2.3					6							
1M8	4.4	4.3					8							
1M10	6.4	6.3					10							
1M12	8.4	8.3					12							
1M14	10.4	10.3					14							
1.125M6		2.3			1.125	-12	6	0.50	0.75	6	1.69	0.61	2.25	0.14
1.125M8		4.3					8							
1.125M10		6.3					10							
1.125M12		8.3					12							
1.25M6		2.3	1.5	1.2	1.25	-12	6	0.50	7/8	6	1.88	0.72	2.50	0.16
1.25M8		4.3	3.5	3.2			8							
1.25M10		6.3	5.5	5.2			10							
1.25M12		8.3	7.5	7.2			12							
1.5M7			2.4	2.0	1.50	-12	7	0.75	1.125	6	2.25	0.84	3.50	0.19
1.5M8			3.4	3.0			8							
1.5M10			5.4	5.0			10							
1.5M12			7.4	7.0			12							
1.5M14			9.4	9.0			14							
1.5M16			11.4	11.0			16							
1.75M8				2.9	1.75	-12	8	0.75	1.25	6	2.75	0.97	4.00	0.21
1.75M10				4.9			10							
1.75M12				6.9			12							
1.75M14				8.9			14							
1.75M16				10.9			16							
2M8				2.8	2.00	-12	8	0.75	1.5	12	3.13	1.09	4.50	0.21
2M10				4.8			10							
2M12				6.8			12							
2M14				8.8			14							
2M16				10.8			16							
NOTES: Not all Leveling Screw Models listed are stocked. Custom Lengths are available.														

NOTE: Data subject to change without notice.

03/29/2019